

SPECIFICATIONEN

(Technische Änderungen, Fehler oder Irrtum vorbehalten)

Model		MVT-9H	
POWER	Power Source	DC 12V Input ± 15%	
	Power Consumption	70mA	
CCD	Image Sensor	1/3" Sony 960H EXview HAD CCD II	
	Effective Pixels	PAL: 976(H) x 582(V) 570K	NTSC:976(H) x 494(V) 480K
DSP	Signal Processor		
SYNC.	Sync.	2:1 Interlaced	
	Scanning Synchronization	Internal / Line-Lock(Analog,Digital) (External Sync Input)	
S/N (Y Signal)		More than 48 dB (AGC off)	
Frequency		Horizontal:15.625KHz/Vertical:50.00Hz(PAL)	Horizontal:15.734KHz/Vertical:59.94Hz(NTSC)
VIDEO	Video Out	1.0Vp-p Composite Signal (75ohm)	
OLPF	OLPF Selection	2 Types	
	Exposure	LENS/BLC/HLM/AGC/2D-DNR	
	Electric Shutter	1/50 ~ 1/100,000s	1/60 ~ 1/100,000s
	WDR	100DB	
	Day/Night	AUTO/DAY/NIGHT/ILC(IR Light Control)	
	Min. Illumination	0.001LUX	
	H. Resolution	700 TV Lines	
	White Balance	ATW/AWB/MANUAL/PUSH(1,700°K ~ 11,000°K)	
	GAMMA	0.45/0.60/1.0/USER	
	2D-DNR	YES	
	Monitor	CRT/LCD	
	LSC	0~30	
	Privacy Masking	8 Privacy mask (variety angle quadrangle and 7 colors)	
	AGC	Shut/low/medium/high	
	MIRROR	YES	
	SHARPNESS	0~30	
	Motion Detection	Off / On	
	RS-485	PELCO-D	
	BaudRate	2400/4800/9600/14400/19200	
	Multi-Language	Chinese/ENGLISH/Traditional Chinese/Korean/ Japanese language/Italian /Russian /Portuguese / Spanish / German / French	
OSD	Available with icon		
Operation Temperature		-10°C ~ +60°C (Humidity: 0% ~ 80%RH)	
Storage Temperature		-20°C ~ +70°C (Humidity: 0% ~ 85%RH)	
Weight		25g (board only)	
Dimension		38mm*38mm/32mm*32mm	